

MAClite 5700

PRODUCT DESCRIPTION

MAClite 5700 is a flexible reflective film (Engineering Grade) providing wide-angle reflectivity of incident light and giving excellent night and day visibility. The film consists of a layer of microscopic glass beads of high optical quality embedded in a coloured film and react as lenses. A metallized back provides the mirror surface for reflection. Thanks to its flexibility, MAClite 5700 is easy to cut and to weed and can be applied on curved or corrugated surfaces.

Face Material: Flexible Engineered Grade reflective film $\pm 115 \mu\text{m}$ thick

Adhesive: High quality white solvent based permanent acrylic adhesive.

Liner: Highly stable 150 gsm white polyethylene coated paper.

TYPICAL USE

MAClite 5700 is a marking film designed for 24 h a day eye-catching decoration and identification. MAClite 5700 is designed for vehicle markings where application on riveted or corrugated surfaces may be required.

PROCESSING

Printing

MAClite 5700 can be printed with some screen inks and varnishes. However assurance of ink performance in all cases should be first obtained from the ink supplier.

Computer cutting

Clean, quick, trouble-free cutting with most plotters.

Application

The transfer of the cut material onto the Application Tape should always be performed by removing the liner from the pressure-sensitive material (i.e. with the film downwards onto the working surface) and not by lifting off the Application Tape. MAClite 5700 can be applied with the dry application method on slightly curved, riveted and embossed surfaces with the aid of a heat gun.

Important remark

All surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination. The compatibility of paints and lacquers should be tested by the end-user, prior to use.

Edge sealing and varnishing

Where exposure to chemicals and solvent spillage is likely to occur, edge sealing of decals with a varnish will prevent edge lift. Correct varnishing of decals gives greater protection, and extends the useful life against prolonged effects of weathering, abrasion and other effects such as frequent cleanings.

SHELF LIFE

1 year when stored at 15 to 25°C and $\pm 50\%$ relative humidity.

PHYSICAL PROPERTIES (TYPICAL VALUES)

Average Values Test Method

Thickness		
Film + Adhesive (mm)	0.150	ASTM D-645
Face Material data, 23°C		
Tensile Strength	> 16 N/15mm	DIN 53455
Elongation at Break (%)	$\geq 100\%$	DIN 53455
Adhesive data, 23°C (N/25 mm)		
Peel adhesion 180° on stainless steel		
- 20 min. residence	24	
- 24 hour residence	34	FTM1
Dimensional stability		
Shrinkage (1 week at 70°C applied on Aluminium)	< 0.3 %	FTM14
Temperature ranges		
Application (°C)	+10°C to + 40°C	
End-use (°C)	- 20°C to + 90°C	

Reflectivity	
At -4° entrance angle and 0.2° observation angle - (cd/lx/sqm)	
	Typical retro reflection
MAClite 5729-00 White	70
MAClite 5709-00 Yellow	50
MAClite 5701-00 Orange	20
MAClite 5759-00 Red	5
MAClite 5739-00 Light Blue	6
MAClite 5739-01 Dark Blue	4
MAClite 5749-00 Green	7
MAClite 5789-00 Black	3
Solvent and chemical resistance	
Resistance to most:	oils and grease, fuel, aliphatic solvents, weak acids, salts and alkalis.

EXPECTED DURABILITY

Central Europe (Zone 1)

5-7 years	ISO4892-3
-----------	-----------

Note : Exposure to severe temperatures and ultraviolet light, as well as conditions in southern European countries, and also in tropical, sub-tropical or desert regions, will cause a more rapid deterioration. This also applies to polluted areas, high altitude, horizontal and south-facing exposure.

DISCLAIMER

For more information on the durability and exposure please visit the “Mactac Technical Bulletin TB 7.5 Outdoor Durability of Mactac Graphics - Self-adhesive films” on the [www.https://www.mactacgraphics.eu](http://www.mactacgraphics.eu) website.

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.